

DILATOFLEX

AN EFFICIENT SOLUTION FOR A WIDE RANGE OF APPLICATIONS

BUILDING INDUSTRY

- ▶ Central heating and air conditioning
- ▶ Hot and cold water systems
- ▶ Fire extinction systems

POWER GENERATION

- ▶ Cooling systems, pumping stations, etc. for conventional and nuclear power plants

PETROLEUM INDUSTRY

- ▶ Cooling systems
- ▶ Fuel handling

NAVAL CONSTRUCTION

- ▶ Machine cooling systems
- ▶ Sanitary installations
- ▶ Fire extinction systems
- ▶ Fuel handling

METALLURGY

- ▶ Blast furnace gas
- ▶ Compressed air
- ▶ Industrial water systems

WATER TREATMENT

- ▶ Production and distribution of drinking water, waste water treatment

FOOD INDUSTRY

- ▶ Drinking water and other beverage and foodstuff handling systems

CHEMICAL INDUSTRY

Fluid handling systems:

- ▶ acids, bases, hydrocarbons, emulsions, solutions, air, gas, steam, water, etc.


Lining Grade Identification colour and designation	Typical Applications	W.T. Working temperatures
Green label CC	▶ Central heating and air conditioning water	-35 °C +90 °C/ 110 °C
Blue label DW	▶ Drinking Water Approved ▶ Domestic cold and hot water	-25 °C +90 °C/ 105 °C
Cream label EPC	▶ Food products ▶ White Food Grade liner ▶ Option Stainless Steel flanges	-25 °C +95 °C
White label ES	▶ Steel Mesh Reinforced ▶ Superheated water ▶ Hot water vapour	-35 °C +140 °C
Red label AR/CN	▶ Abrasive or corrosive products (weak acids and bases) ▶ Industrial water, sea water ▶ Low-temperature water vapour	-35 °C +90 °C
Orange label GZ	▶ Gas, compressed air, fuel, oil ▶ Petroleum products with aromatic content < 40% ▶ Sanitation water	-20 °C +90 °C
Blue label HH	▶ Industrial and waste water ▶ Hydrogen gas, nitrogen	-20 °C +90 °C
Yellow label YP	▶ Strong acids ▶ Strong bases ▶ Aggressive chemicals	-25 °C +100 °C
Grey label AB	▶ Strong acids ▶ Strong bases ▶ Weak chlorinated products	-35 °C +100 °C
Mauve label TE	▶ Industrial water ▶ Acidic water ▶ Diluted acids and bases	-25 °C +100 °C
White label F1	▶ Special highly aggressive products (Working pressure limited to 6 bar max.)	-35 °C +110 °C




The inner lining to be used for a specific fluid (composition, concentration, temperature, etc.) should be selected according to our Chemical Resistance Chart.

Distributor : **Mercia Flexibles** • www.merciaflexibles.co.uk
Ludlow Eco Park • Ludlow • Shropshire • SY8 1FF • UK
Tel.: +44 (0)1584 874999 • Email: dilatoflex@merciaflexibles.co.uk


Operating Principles




AXIAL COMPRESSION




AXIAL ELONGATION




LATERAL DEFLECTION



ANGULAR DEFLECTION



WATER HAMMER REDUCTION



ELIMINATION OF VIBRATION